



Auszug: Baulängen nach EN 558 (Durchgangsform)
Extract: face to face dimensions acc. to EN 558 (straight pattern)

	R 1	R 14	R 15	R 16	R 20	R 25	R 49	R 52	
10	130	115	-	-	-	-	-	-	
15	130	115	-	-	-	-	16	25	
20	150	120	-	-	25	-	19	31,5	
25	160	125	120	-	25	-	22	35,5	
32	180	130	140	-	33	-	28	40	
40	200	140	240	33	33	-	31,5	45	
50	230	150	250	43	43	-	40	56	
65	290	170	270	46	46	-	46	63	
80	310	180	280	64	46	49	50	71	
100	350	190	300	64	52	56	60	80	
125	400	200	325	70	56	64	90	110	
150	480	210	350	76	56	70	106	125	
200	600	230	400	89	60	71	140	160	
250	730	250	450	114	68	76	-	200	
300	850	270	500	114	78	83	-	250	
350	980	290	550	127	78	92	-	280	
400	1100	310	600	140	102	102	-	-	
450	1200	330	650	152	114	114	-	-	
500	1250	350	700	152	127	127	-	-	
600	1450	390	800	178	154	154	-	-	
700	1650	430	900	229	165	-	-	-	
800	1850	470	1000	241	190	-	-	-	
900	1050	510	1100	241	(200) 203	-	-	-	
1000	2250	550	1200	300	(251) 216	-	-	-	
1200	-	630	-	350	(276) 254	-	-	-	
1400	-	710	-	390	279	-	-	-	
1600	-	790	-	440	318	-	-	-	
1800	-	870	-	490	356	-	-	-	
2000	-	950	-	540	406	-	-	-	
= DIN 3202:	F1	F4	F5	K3	K1	K2	K4	K5	
Verwendung möglich z.B. bei: Application possib- le for (e.g.):	Kugelhähne / ball valves PN 6, 10, 16, 25, 40 Membranarmaturen / diaphragm fittings PN 6, 10, 16, 25, 40 Ventile / valves PN 6, 10, 16, 25, 40 Flansch-Rückfluss- verhinderer / flanged check valves PN 6, 10, 16, 25, 40 Regelventile / control valves PN 10, 16, 25, 40	Schieber / gate valves PN 6, 10, 16 Flansch-Klappen / flanged butterfly valves PN 10, 16, 25, 40 Ventile / valves PN 10, 16, 25, 40 Flansch-Rück- flussverhinderer / flanged check valves PN 6, 10, 16	Schieber / gate valves PN 6, 10, 16	Einklemm- Klappen wafer type butterfly valves PN 6, 10, 16, 25, 40 Einklemm-Rück- flussverhinderer wafer type check valves PN 6, 10, 16, 25, 40	Einklemm- Klappen wafer type butterfly valves PN 6, 10	Einklemm- Klappen wafer type butterfly valves PN 6, 10, 16, 25, 40	Einklemm-Rück- flussverhinderer wafer type check valves PN 6, 10, 16, 25, 40		